

— " FLANGED (250 PSI) COUPLING ADAPTOR TO FIT
 — " O.D. STEEL PIPE WITH THREE SETS OF
 HARNESS CLIPS (SEE DWG. DD-902-02).

— " DUO-CHEK CHECK VALVE (— PSI)
 2- — " SLIP-ON FLANGE (— PSI)

DIFFERENTIAL PRESSURE LINE ASSEMBLY
 (FOR VARIABLE SPEED ONLY)
 (SEE DWG. DD-901-03).

CONCRETE HIGH SERVICE
PUMP SLAB
 (SEE DWG. DD-901-01).

CONCRETE PIPE SUPPORT
 (SEE DWG. DD-901-01).

1" PLATE DETAIL
 (SEE DWG. DD-901-02).

DIFFERENTIAL PRESSURE SWITCH
 (SEE DWG. DD-901-03).

— " BALL VALVE, FLG. (250 PSI)
 — " SLIP-ON FLG. (250 PSI)

— " FABRICATED STEEL
 45 DEG. BEND,

2- — " STEEL COUPLING TO FIT
 — " O.D. STEEL PIPE WITH THREE
 SETS OF HARNESS CLIPS.
 COAT AND WRAP ALL BURIED
 COUPLINGS AS PER SPECIFICATIONS.
 (SEE DWG. DD-902-04).

DISCHARGE HEADER
 — " X — " TEE, FLG.
 — " BUTTERFLY VALVE, FLG.
 6" VALVE BOX, COMPLETE
 — " SLIP-ON FLG.

— " FABRICATED STEEL
 45 DEG. BEND WITH
 CONC. REACTION BLOCK

15'-9" MIN.

